

Prepared For:
STOCK
LANCE WILLIAMS
2100 E 29TH ST
MARSHFIELD, WI 54449-
(715)591 - 2591

Presented By:
MID-STATE TRUCK SV INC
LANCE WILLIAMS
2100 E. 29TH ST
MARSHFIELD WI 54449 - 7150
(715)406-4266

Thank you for the opportunity to provide you with the following quotation on a new International truck. I am sure the following detailed specification will meet your operational requirements, and I look forward to serving your business needs.

Model Profile
2011 7500 SBA 6X4 (SF637)

MISSION: Requested GVWR: 58000. Calc. GVWR: 60000

DIMENSION: Wheelbase: 187.00, CA: 119.90, Axle to Frame: 75.00

ENGINE, DIESEL: {International MaxxForce 10} EPA 07, 350 HP 1150 lb-ft Torque @ 1200 RPM, 2200 RPM Governed Speed, # 2 Bell Housing

TRANSMISSION, AUTOMATIC: {Allison 3000_RDS_P} 4th Generation Controls; Close Ratio, 6-Speed, With Double Overdrive; On/Off Hwy; Includes Oil Level Sensor, With PTO Provision, Less Retarder, With 80,000-lb GVW & GCW Max.

CLUTCH: Omit Item (Clutch & Control)

AXLE, FRONT NON-DRIVING: {Meritor MFS-20-133A} Wide Track, I-Beam Type, 20,000-lb Capacity

AXLE, REAR, TANDEM: {Meritor RT-40-145} Single Reduction, 0.433" Wall Housing Thickness, 40,000-lb Capacity, R Wheel Ends, Driver Controlled Locking Differential in Forward Rear and Rear Rear Axle Gear Ratio: 6.43

CAB: Conventional

TIRE, FRONT: (2) 315/80R22.5 HSU2 (CONTINENTAL) 481 rev/mile, load range L, 20 ply

TIRE, REAR: (8) 11R22.5 HDR1 (CONTINENTAL) 495 rev/mile, load range G, 14 ply

SUSPENSION, REAR, TANDEM: {Hendrickson HMX-400-54} Walking Beam Type 54" Axle Spacing; 40,000-lb Capacity, With Rubber End Bushings, Transverse Torque Rods, Less Shock Absorbers

PAINT: Cab schematic 100GN
Location 1: 2303, Red (Std)
Chassis schematic N/A

<u>Code</u>	<u>Description</u>	<u>F/R Wt</u> (lbs)	<u>Tot Wt</u> (lbs)
SF63700	Base Chassis, Model 7500 SBA 6X4 with 187.00 Wheelbase, 119.90 CA, and 75.00 Axle to Frame.	7628/6174	13802
1572	TOW HOOK, REAR (2)	0/10	10
1CAJ	FRAME RAILS Heat Treated Alloy Steel (120,000 PSI Yield); 10.866" x 3.622" x 0.433" (276.0mm x 92.0mm x 11.1mm); 456.0" (11582mm) Maximum OAL	198/402	600
1LLK	BUMPER, FRONT Omit Item	-92/16	-76
1WDS	FRAME EXTENSION, FRONT Integral; 20" In Front of Grille	139/-34	105
1WGX	WHEELBASE RANGE 169" (430cm) Through and Including 219" (555cm)	0/0	0
2ARY	AXLE, FRONT NON-DRIVING {Meritor MFS-20-133A} Wide Track, I-Beam Type, 20,000-lb Capacity	141/0	141
3AGA	SUSPENSION, FRONT, SPRING Parabolic, Taper Leaf; 20,000-lb Capacity; With Shock Absorbers	73/0	73
4091	BRAKE SYSTEM, AIR Dual System for Straight Truck Applications	0/0	0
4193	BRAKES, FRONT, AIR CAM 16.5" x 6", Includes 24 SqIn Long Stroke Brake Chambers	-62/0	-62
4732	DRAIN VALVE {Berg} Manual; With Pull Chain, for Air Tank	0/0	0
4AZA	AIR BRAKE ABS {Bendix AntiLock Brake System} Full Vehicle Wheel Control System (4-Channel)	0/0	0
4EBD	AIR DRYER {Meritor Wabco System Saver 1200} with Heater	11/7	18
4ETE	BRAKE CHAMBERS, FRONT AXLE {Haldex} 24 SqIn	4/0	4
4EVL	BRAKE CHAMBERS, REAR AXLE {Haldex GC3030LHDHO} 30/30 Spring Brake	0/0	0
4LAA	SLACK ADJUSTERS, FRONT {Haldex} Automatic	6/0	6
4LGA	SLACK ADJUSTERS, REAR {Haldex} Automatic	0/0	0
4NDB	BRAKES, REAR, AIR CAM S-Cam; 16.5" x 7.0"; Includes 30/30 Sq.In. Long Stroke Brake Chamber and Spring Actuated Parking Brake	0/0	0
4SBC	AIR COMPRESSOR {Bendix Tu-Flo 550} 13.2 CFM Capacity	0/0	0
5708	STEERING COLUMN Tilting	10/0	10
5CAL	STEERING WHEEL 2-Spoke, 18" Diam., Black	0/0	0
5PTB	STEERING GEAR (2) {Sheppard M-100/M-80} Dual Power	50/0	50
7BEJ	EXHAUST SYSTEM Single, Horizontal, Aftertreatment Device Frame Mounted Outside Right Rail Under Cab; Includes Vertical Tail Pipe and Guard	0/0	0
7SCJ	EXHAUST BRAKE, DLOGIC {Diamond Logic} for MaxxFORCE 9 / DT570, MaxxFORCE 10 / HT570 Engines; Electronically Activated	0/0	0
7WAZ	TAIL PIPE (1) Turnback Type, Non-Bright, for Single Exhaust	0/0	0
7WZY	SWITCH, FOR EXHAUST 2 Position, Lighted & Latching, ON/OFF Type, Mounted in IP, Inhibits Diesel Particulate Filter Regeneration as Long as Switch is in ON Position	2/0	2
8000	ELECTRICAL SYSTEM 12-Volt, Standard Equipment	0/0	0
8518	CIGAR LIGHTER Includes Ash Cup	1/0	1

<u>Code</u>	<u>Description</u>	<u>F/R Wt</u> (lbs)	<u>Tot Wt</u> (lbs)
8GHC	ALTERNATOR {Leece-Neville LBP2203H} Brush Type, 12 Volt 160 Amp. Capacity, Pad Mounted	-6/0	-6
8HAB	BODY BUILDER WIRING Back of Standard Cab at Left Frame or Under Extended or Crew Cab at Left Frame; Includes Sealed Connectors for Tail/Amber Turn/Marker/ Backup/Accessory Power/Ground and Sealed Connector for Stop/Turn	2/0	2
8MEZ	BATTERY SYSTEM {International} Maintenance-Free, (2) 12-Volt 1850CCA Total	0/0	0
8RJV	RADIO {International} AM/FM Stereo With Weatherband, Clock, Auxiliary Input, Includes Multiple Speakers	3/0	3
8THJ	AUXILIARY HARNESS 3.0' for Auxiliary Front Head Lights and Turn Signals for Front Plow Applications	2/0	2
8VZR	SWITCH, BODY CIRCUITS, MID ; for Bodybuilder, 6 Switches in Instrument Panel; One Power Module with 6 Channels, 20 Amp Max. Per Channel, 80 Amp Max Output, Switches Control Power Module Through Multiplex Wiring, Mounted in Cab Behind Driver Seat	0/0	0
8WCL	HORN, AIR Black, Single Trumpet, Air Solenoid Operated	0/0	0
8WEL	BATTERY BOX Steel, With Fiberglass Cover; Mounted 26" BOC, Left Side Perpendicular to Frame Rail	0/0	0
8WML	HEADLIGHTS Long Life Halogen; for Two Light System	0/0	0
8WTK	STARTING MOTOR {Delco Remy 38MT Type 300} 12 Volt; less Thermal Over-Crank Protection	0/0	0
8WWJ	INDICATOR, LOW COOLANT LEVEL With Audible Alarm	1/0	1
8XAH	CIRCUIT BREAKERS Manual-Reset (Main Panel) SAE Type III With Trip Indicators, Replaces All Fuses Except For 5-Amp Fuses	0/0	0
9585	FENDER EXTENSIONS Rubber	6/0	6
9HBM	GRILLE Stationary, Chrome	0/0	0
9WAC	BUG SCREEN Front End; Mounted Behind Grille	5/0	5
9WBC	FRONT END Tilting, Fiberglass, With Three Piece Construction; for 2007 Emissions	0/0	0
10060	PAINT SCHEMATIC, PT-1 Single Color, Design 100	0/0	0
10761	PAINT TYPE Base Coat/Clear Coat, 1-2 Tone	0/0	0
11001	CLUTCH Omit Item (Clutch & Control)	-91/-16	-107
12851	PTO EFFECTS, ENGINE FRONT Less PTO Unit, Includes Adapter Plate on Engine Front Mounted	10/0	10
12NSY	ENGINE, DIESEL {International MaxxFORCE 10} EPA 07, 350 HP 1150 lb-ft Torque @ 1200 RPM, 2200 RPM Governed Speed, # 2 Bell Housing	0/0	0
12THT	FAN DRIVE {Horton Drivemaster} Direct Drive Type, Two Speed With Residual Torque Device for Disengaged Fan Speed	10/0	10
12UWY	RADIATOR Cross Flow, Series System; 1228 SqIn Aluminum Radiator Core and 1167 SqIn Charge Air Cooler	0/0	0
12UXW	FEDERAL EMISSIONS for 2004; for International HT570 Engines	0/0	0
12VAG	AIR CLEANER Single Element, with Integral Snow Valve and In-Cab Control	2/0	2

<u>Code</u>	<u>Description</u>	<u>F/R Wt</u> (lbs)	<u>Tot Wt</u> (lbs)
12VXT	THROTTLE, HAND CONTROL Engine Speed Control; Electronic, Stationary, Variable Speed; Mounted on Steering Wheel	0/0	0
12VYL	ACCESSORY WIRING, SPECIAL for Road Speed Wire Coiled Under Instrument Panel for Customer Use	0/0	0
12VYP	ENGINE CONTROL, REMOTE MOUNTED - No Provision Furnished for Remote Mounted Engine Control	0/0	0
12VYW	FEDERAL EMISSIONS 2007 for International MaxxForce 9 & 10 Engines (DT570 & HT570)	0/0	0
12WTH	BLOCK HEATER, ENGINE {Phillips} 120 Volt/1250 Watt; With "Y" Cord From Socket in Standard Location, For a Dealer Installed Oil Pan Heater, With Extended Life Coated Metal/Plastic/Metal Material Oil Pan, for I6	4/0	4
12WYS	EXPANDED ENGINE TEMP EFFECTS to Allow Higher Engine Operating Temperature Range; Includes Nylon Surge Tank and 15 psi Pressure Cap	0/0	0
12WZE	EMISSION COMPLIANCE Federal, Does Not Comply With California Clean Air Regulations	0/0	0
13AMB	TRANSMISSION, AUTOMATIC {Allison 3000_RDS_P} 4th Generation Controls; Close Ratio, 6-Speed, With Double Overdrive; On/Off Hwy; Includes Oil Level Sensor, With PTO Provision, Less Retarder, With 80,000-lb GVW & GCW Max.	196/56	252
13AWA	OIL COOLER, AUTO TRANSMISSION {Modine} Water to Oil, for Allison or CEEMAT Transmission	25/0	25
13WBL	TRANSMISSION SHIFT CONTROL {Allison} Push-Button Type; for Allison 3000 & 4000 Series Transmission	0/0	0
13WDY	SHIFT CONTROL PARAMETERS WT-Allison S-1 Performance Programming in Primary and Allison S-4 Economy Programming in Secondary	0/0	0
13WLP	TRANSMISSION OIL Synthetic; 29 thru 42 Pints	0/0	0
13WUC	ALLISON SPARE INPUT/OUTPUT for Rugged Duty Series (RDS); General Purpose Trucks, Construction	0/0	0
13WYH	TRANSMISSION TCM LOCATION Located Inside Cab	0/0	0
14GWD	AXLE, REAR, TANDEM {Meritor RT-40-145} Single Reduction, 0.433" Wall Housing Thickness, 40,000-lb Capacity, R Wheel Ends, Driver Controlled Locking Differential in Forward Rear and Rear Rear Axle . Gear Ratio: 6.43	0/26	26
14ULX	SUSPENSION, REAR, TANDEM {Hendrickson HMX-400-54} Walking Beam Type 54" Axle Spacing; 40,000-lb Capacity, With Rubber End Bushings, Transverse Torque Rods, Less Shock Absorbers	0/9	9
14WAL	SUSPENSION/REAR-AXLE IDENTITY for Meritor Tandem Rear Axles With Bar-Pin Beam Attachment Type Suspensions	0/0	0
15LKG	FUEL/WATER SEPARATOR With Thermostatic Fuel Temperature Controlled Electric Heater, and Filter Restriction/Change Indicator, Includes Standard Equipment Water-in-Fuel Sensor	5/0	5
15SGG	FUEL TANK Top Draw; D Style, Non Polished Aluminum, 19" Deep, 70 U.S. Gal., 265 L Capacity, With Quick Connect Outlet, Mounted Left Side, Under Cab	-33/-13	-46
16030	CAB Conventional	0/0	0
16HBA	GAUGE CLUSTER English With English Electronic Speedometer	0/0	0

<u>Code</u>	<u>Description</u>	<u>F/R Wt</u> (lbs)	<u>Tot Wt</u> (lbs)
16HGH	GAUGE, OIL TEMP, ALLISON TRAN	1/0	1
16HHE	GAUGE, AIR CLEANER RESTRICTION {Filter-Minder} With Black Bezel Mounted in Instrument Panel	2/0	2
16HKA	IP CLUSTER DISPLAY Omit Display of Fault Codes in Instrument Cluster and Disable Blink Codes, Requires Service Tool to Retrieve and View Fault Code	0/0	0
16JNV	SEAT, DRIVER {National 2000} Air Suspension, High Back With Integral Headrest, Cloth, Isolator, 1 Chamber Lumbar, 2 Position Front Cushion Adjust, -3 to +14 Degree Back Angle Adjust	0/0	0
16PJU	SEAT, PASSENGER {Gra-Mag} Non Suspension, High Back With Integral Headrest, Cloth, With Fixed Back, With Under Seat Storage	53/23	76
16SDL	MIRRORS (2) {Lang Mekra} Rectangular, 7.44" x 14.84" & 7.44" sq. Convex Both Sides, 102" Inside Spacing, Breakaway Type, Heated Heads Thermostatic Controlled, Black Heads, Brackets and Arms	0/0	0
16SEE	GRAB HANDLE Chrome; Towel Bar Type With Anti-Slip Rubber Inserts; for Cab Entry Mounted Left Side Only at "B" Pillar	3/0	3
16WBY	ARM REST, RIGHT, DRIVER SEAT	3/0	3
16WEE	CAB SOUND INSULATION Includes Dash Insulator and Engine Cover Insulator	12/0	12
16WJT	INSTRUMENT PANEL Center Section, Ergonomic Panel	0/0	0
16WJU	WINDOW, POWER (2) And Power Door Locks, Left and Right Doors, Includes Express Down Feature	5/0	5
16WKB	AIR CONDITIONER {International Blend-Air} With Integral Heater & Defroster	60/0	60
16WKY	HVAC FRESH AIR FILTER	0/0	0
16WLE	STORAGE POCKET, DOOR Molded Plastic, Full Width; Mounted on Passenger Door	1/0	1
16WRX	CAB INTERIOR TRIM Deluxe	0/0	0
16WSK	CAB REAR SUSPENSION Air Bag Type	0/0	0
16XXC	COWL TRAY LID	0/0	0
27DPL	WHEELS, FRONT DISC; 22.5" Painted Steel, 5 Hand Hole, 10-Stud (285.75MM BC) Hub Piloted, Flanged Nut, Metric Mount, 9.00 DC Rims; With .500" Thick Disc, Non-Standard Offset and Steel Hubs	122/0	122
28DMA	WHEELS, REAR DUAL DISC; 22.5" Painted Steel, 2 Hand Hole, 10-Stud (285.75MM BC) Hub Piloted, Flanged Nut, Metric Mount, 8.25 DC Rims; With Steel Hubs	0/0	0
7372135418	(8) TIRE, REAR 11R22.5 HDR1 (CONTINENTAL) 495 rev/mile, load range G, 14 ply	0/8	8
7792545416	(2) TIRE, FRONT 315/80R22.5 HSU2 (CONTINENTAL) 481 rev/mile, load range L, 20 ply	84/0	84
Total Component Weight:		8596/6668	15264

The weight calculations included in this proposal are an estimate of future vehicle weight. The actual weight as manufactured may be different from the estimated weight. Navistar, Inc. shall not be liable for any consequences resulting from any differences between the estimated weight of a vehicle and the actual weight.